

INDIRECT FIRED HEATERS



FVP-400



FVO-400

MODEL	FVO-400 Oil	FVN-400 Natural Gas	FVP-400 Propane
Heat Capacity	390,000 btuh	390,000 btuh	390,000 btuh
Fuel Tank Capacity	42 US gallons	External n/a	External n/a
Operating Time/ Fuel Consumption	14 hours 2.75 gal/hr	380 CFH	18.5 lbs/hr
L x W x H	70"x 29"x 52"	70"x 29"x 47"	70"x 29"x 47"
Heat Exchanger	16 gauge 304 Stainless Steel	16 gauge 304 Stainless Steel	16 gauge 304 Stainless Steel
Fan Motor	3/4 HP@1,725 rpm 2,500 CFM	3/4 HP@1,725 rpm 2,500 CFM	3/4 HP@1,725 rpm 2,500 CFM
Ignition	Direct Spark Ignition	Direct Spark Ignition	Direct Spark Ignition
Nozzle Size/ Gas Pressure	2.25 x 45B (@)150 PSI	2.0" W.C.	3.2" W.C.
Air Outlet (optional)	Two 12" diameter One 16" diameter	Two 12" diameter One 16" diameter	Two 12" diameter One 16" diameter
Wheels	Two 16" diameter Pneumatic wheels	Two 16" diameter Pneumatic wheels	Two 16" diameter Pneumatic wheels
Power Requirement	115V/15Amp	115V/15Amp	115V/15Amp
Approvals	cETLus	cETLus	cETLus
Weight	450 lbs	365 lbs	365 lbs

DEPENDABLE HEAT WHEREVER YOU NEED IT

170° F - 180° F outlet temperature rise
 Includes proven Riello burner technology
 Optional remote thermostat available
 ETL approved for use in the United States and Canada
 FVO-200 has a stackable frame for easy storage

