

**CURE-CRETE PLUS VOC - 5 GAL PAIL**Version 2.  
REVISION DATE: 04/08/2011

Print Date 04/21/2011

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : CURE-CRETE PLUS VOC - 5 GAL PAIL  
 Product code : CCUV G005 000

COMPANY : Increte Systems - A Division of The Euclid Chemical Company  
 1611 Gunn Highway  
 Odessa, FL 33556

Telephone : 1-800-752-4626  
 Emergency Phone: : U.S. only: 1-800-424-9300  
 International Users Call Collect: 1-703-527-3887

Product use : Coating

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Clear. Liquid. May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue.

Eyes : Vapor and/or mist may cause eye irritation. Direct contact may cause temporary redness and discomfort.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause moderate irritation.


**Aggravated Medical Conditions**

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Prolonged or repeated contact/exposure to aromatic petroleum distillates may cause defatting, drying, and irritation of the skin, dermatitis, and central nervous system (CNS) effects. Di(2-ethylhexyl) phthalate, (dioctyl phthalate) given in the diet, produced increased incidence of liver cancers in female rats and male and female mice. An increased incidence of liver cancers or neoplasms were observed in male rats. T-Butyl alcohol, when given to mice at very high doses, has been reported to damage the developing fetus, kidneys and to cause tumors in rats and mice. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**Target Organs:** Skin, Eye, Lung, Liver, Kidney, Nerve, Reproductive

**CURE-CRETE PLUS VOC - 5 GAL PAIL**Version 2.  
REVISION DATE: 04/08/2011

Print Date 04/21/2011

**SECTION 3 - PRODUCT COMPOSITION**

<b>Chemical Name</b>	<b>CAS-No.</b>	<b>Weight %</b>
Tert-Butyl Acetate	540-88-5	40.0 - 70.0
Styrene Ethylhexyl Acrylate Copolymer	NJ TSRN# 51721300-5841P	15.0 - 40.0
Aromatic petroleum distillates	64742-95-6	7.0 - 13.0
1,2,4-Trimethylbenzene	95-63-6	3.0 - 7.0
Dioctyl phthalate	117-81-7	1.0 - 5.0


**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

Inhalation	:	Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
Skin contact	:	Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

Flash point	:	11 °C, 52 °F
Method	:	Not available.
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	:	Smoke, fumes. Carbon monoxide and carbon dioxide can form. Nitrogen oxides can form.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water may be used to cool containers to minimize pressure build-up.
Fire and explosion conditions	:	Vapor concentrations in enclosed areas may ignite explosively. Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flashback. Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors.



**CURE-CRETE PLUS VOC - 5 GAL PAIL**

Version 2.  
REVISION DATE: 04/08/2011

Print Date 04/21/2011

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Keep container closed when not in use. Vapor may migrate to sources of ignition. Do not smoke, weld, generate sparks, or use flame near container. Store in sealed containers in a cool, dry, ventilated warehouse location.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Protective measures : Use professional judgment in the selection, care, and use. Inspect and replace equipment at regular intervals.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Tert-Butyl Acetate	540-88-5	ACGIH TWA: OSHA PEL:	200 ppm 950 mg/m3	
1,2,4-Trimethylbenzene	95-63-6	ACGIH TWA:	25 ppm	
Diocetyl phthalate	117-81-7	ACGIH TWA: OSHA PEL:	5 mg/m3 5 mg/m3	



**CURE-CRETE PLUS VOC - 5 GAL PAIL**

Version 2.  
REVISION DATE: 04/08/2011

Print Date 04/21/2011

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Form	: Liquid
Color	: Clear
Odor	: Aromatic Solvent
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: 98 °C, 208 °F
Water solubility	: Negligible
Specific Gravity	: 0.9095
% Volatile Weight	: 72.2 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid	: Oxidizing agents.Strong acids.Strong bases.
Stability	: Stable under normal conditions. Avoid welding arcs, flames or other high temperature sources.
Hazardous polymerization	: Will not occur.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Diocetyl phthalate, CAS-No.: 117-81-7	
Acute oral toxicity (LD-50 oral)	25,000 mg/kg ( Rat ) 25,000 mg/kg ( Rat ) 30,000 mg/kg ( Mouse ) 33,900 mg/kg ( Rabbit ) 26,300 mg/kg ( Guinea pig )
Acute dermal toxicity (LD-50 dermal)	25,000 mg/kg ( Rabbit ) 10,000 mg/kg ( Guinea pig ) 25,000 mg/kg ( Rabbit )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

RCRA Class	: D001: Reportable Quantity = 100 lbs. (Characteristic of ignitability) This classification applies only to the material as it was originally produced.
Disposal Method	: Subject to hazardous waste treatment, storage, and disposal requirements under



**CURE-CRETE PLUS VOC - 5 GAL PAIL**

Version 2.  
REVISION DATE: 04/08/2011

Print Date 04/21/2011

RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**TDG / DOT Shipping Description:**

UN1139, COATING SOLUTION, 3, PG II

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : 1,2,4-Trimethylbenzene 95-63-6  
Diocetyl phthalate 117-81-7

SARA 311/312 Hazards : Acute Health Hazard  
Fire Hazard

OSHA Hazardous Components :

Tert-Butyl Acetate 540-88-5  
1,2,4-Trimethylbenzene 95-63-6  
Diocetyl phthalate 117-81-7

OSHA Status: Considered : Irritant  
hazardous based on the  
following criteria:

OSHA Flammability : IB

Regulatory VOC (less water and : 324 g/l  
exempt solvent)

VOC Method 310 : 13 %

**U.S. State Regulations:**

MASS RTK Components : Tert-Butyl Acetate 540-88-5  
1,2,4-Trimethylbenzene 95-63-6  
Diocetyl phthalate 117-81-7

Penn RTK Components : Tert-Butyl Acetate 540-88-5  
Styrene Ethylhexyl Acrylate Copolymer NJ TSRN# 51721300-5841P  
Aromatic petroleum distillates 64742-95-6  
1,2,4-Trimethylbenzene 95-63-6  
Diocetyl phthalate 117-81-7

NJ RTK Components : Tert-Butyl Acetate 540-88-5  
Styrene Ethylhexyl Acrylate Copolymer NJ TSRN# 51721300-5841P



**CURE-CRETE PLUS VOC - 5 GAL PAIL**

Version 2.

Print Date 04/21/2011

REVISION DATE: 04/08/2011

Aromatic petroleum distillates	64742-95-6
1,2,4-Trimethylbenzene	95-63-6
Dioctyl phthalate	117-81-7

Components under California Proposition 65:  
**WARNING!** Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	1
Flammability	3
Reactivity	0
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

- |  |  |
|--|--|
| ACGIH - American Conference of Governmental Hygienists                         | PEL - Permissible Exposure Limit                         |
| CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act | RCRA - Resource Conservation and Recovery Act            |
| DOT - Department of Transportation   | RTK - Right To Know                                      |
| DSL - Domestic Substance List  | SARA - Superfund Amendments and Reauthorization Act      |
| EPA - Environmental Protection Agency  | STEL - Short Term Exposure Limit                         |
| HMIS - Hazardous Materials Information System                                  | TLV - Threshold Limit Value                              |
| IARC - International Agency for Research on Cancer                             | TSCA - Toxic Substances Control Act                      |
| MSHA - Mine Safety Health Administration                                       | TWA - Time Weighted Average                              |
| NDSL - Non-Domestic Substance List   | V - Volume   |
| NIOSH - National Institute for Occupational Safety and Health                  | VOC - Volatile Organic Compound                          |
| NTP - National Toxicology Program  | WHMIS - Workplace Hazardous Materials Information System |
| OSHA - Occupational Safety and Health Administration                           |  |