



SPRAY DECK SYSTEM

PRODUCT NAME

SPRAY DECK SYSTEM
MANUFACTURER & DISTRIBUTOR
OF INDUSTRIAL CHEMICALS
1611 GUNN HIGHWAY
ODESSA, FLORIDA 33556
(813) 886-8811

PRODUCT DESCRIPTION

SPRAY DECK is a specially formulated textured overlay system designed as a cover-up for a variety of existing concrete and masonry surfaces. From residential to commercial and industrial applications on horizontal or vertical surfaces, Spray-Deck is the ideal cover-up for unsightly existing concrete and masonry. Spray-Deck's unique resin emulsion system is specifically designed for a variety of substrates, including concrete, masonry, bricks, glass, metal, and wood. Do not use on asphalt.

BENEFITS

SPRAY DECK textured overlay system is the answer to revitalizing unsightly pool decks and patios without the need to remove or cap as long as the base is structurally sound.

APPLICATION

Surface Preparation – Surface to be coated must be structurally sound and clean. Always repair unsound substrates before applying materials. If necessary, prepare the substrates by removing all loose and disintegrated material. Oil, grease, or other chemicals should be removed with a detergent, and the detergent should be removed by several washings with water. Because of the excellent adhesion of the Resin, etching or roughening of the surface is not required. Because of the surface skinning characteristics of the mixture, the mortar should be placed as quickly as possible and in the same manner as unmodified mortar.

Mixing Instructions – Mix 3 quarts of SPRAY DECK RESIN and 3 quarts of clean, cool water. Stir in appropriate amount of LIQUID GROUT COLORANT if desired. (Note: For best results when using LIQUID GROUT COLORANT, pre-blend enough resin, water and colorant to complete the entire job.) Add one 50 lb. Bag of grout mix (of desired base color) to liquids in a mixing pail. Thoroughly mix with 1/2" drill with paddle (5 AMP minimum) until proper consistency is reached. Allow mix to set five to ten minutes in mixing pail. Then refresh by mixing and, if necessary, adding small amounts of water to obtain desired consistency for spraying. Spray coverage should be approximately 150 square ft. per mix.

Spread with trowel to desired thickness using a swimming pool or plastering trowel.

One properly prepared 50 lb. Bag of Spray-Deck grout at a thickness of 1/8" should cover approximately 50 to 60 square ft.

Pot life and set time of Mix are 1-2 hours and 4-6 hours respectively under ambient temperatures and humidities. Pot life will decrease at higher temperatures and under conditions of low humidity and/or rapid air movement. Do not apply this product below 55°F. Room temperature (68-77°F) and 50-60% relative humidity conditions are considered ideal for interior/exterior applications. After thorough drying, complete the job by applying INCRETE SYSTEM'S CONCRETE STAIN SEALER or CLEAR SEAL.

Do not use dirty pails or equipment. Mixing equipment must be cleaned immediately after use with clean water.

RECOMMENDED

For use on any sound, concrete and masonry substrate either vertical or horizontal.

AVAILABILITY

Available through distributors or contact manufacturer.

PACKAGING

SPRAY DECK RESIN:

1 gallon, 5 gallon.

SPRAY DECK GROUT:

50 lb. Bags

LIQUID GROUT COLORANT:

1 quart bottles.

COLORS

SPRAY DECK GROUT is available in White, Gray, and Buff.

*LIQUID COLOR DISPERSION GROUT COLORANT is available in the following colors:

- White
- Plum
- Gray
- Charcoal
- Slate
- Kool White
- Misty Mauve
- Maplewood
- Autumn Brown
- Tile Red
- Safety Yellow
- Sun Buff
- Black
- Brick Red
- Rust Brown
- Peach
- Walnut
- Navy Blue
- Pewter
- Redwood
- Sun Gray
- Sky Blue
- Philly Blue
- Harvest Sand
- Sand Buff
- Antique White
- Terra Cotta
- Seafoam Green
- Adobe Buff
- Desert Tan
- Teal
- Sabal
- Coral
- Caribou Tan
- Forrest Green

*Contact your Increte Systems sales rep for information on which SPRAY DECK GROUT color to use with LIQUID GROUT COLORANTS.

WARRANTY

All recommendations, statements and technical data contained herein based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his use of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person having any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations or statements other than those contained in written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

IMPORTANT NOTICE

THESE PRODUCTS ARE SOLD SUBJECT ONLY TO THE EXPRESSED WARRANTIES CONTAINED HEREIN. ADDITIONAL WARRANTIES, EXPRESSED OR IMPLIED, AND ANY WARRANTY OF MERCHANT ABILITY IS HEREBY EXCLUDED. BUYER AGREES THAT SELLER ASSUMES NO LIABILITY FOR CONSEQUENTIAL DAMAGES OF ANY KIND, WHICH RESULT FROM THE USE OR MISUSE OF THE MERCHANDISE SOLD HEREUNDER. IN THE EVENT THAT THE BUYER PROVES THAT ANY GOODS RECEIVED DO NOT CONFORM TO THE SPECIFICATIONS AGREED TO BETWEEN THE PARTIES OR IF THE BUYER PROVES THAT SUCH GOODS WERE DEFECTIVELY MANUFACTURED. THE BUYER'S REMEDIES SHALL BE LIMITED TO EITHER THE RETURN OF THE GOODS AND REPAYMENT OF THE PURCHASE PRICE OR REPLACEMENT OF THE NON-CONFORMING GOODS AT THE OPTION OF THE SELLER. SUCH REMEDY BEING EXCLUSIVE OF ALL OTHERS AND THE SOLE REMEDY AVAILABLE TO THE BUYER, HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES.