



THIN-CRETE GROUT

PRODUCT NAME

THIN-CRETE GROUT

MANUFACTURER & DISTRIBUTOR
OF INDUSTRIAL CHEMICALS
1611 GUNN HIGHWAY
ODESSA, FLORIDA 33556
(813) 886-8811

PRODUCT DESCRIPTION

Increte Systems THIN-CRETE GROUT is an easy to use, polymer-modified, cementitious, stampable overlay. THIN-CRETE is designed for use on either new or worn concrete substrates. THIN-CRETE's polymer modification promotes excellent adhesion, toughness, and long term durability. THIN-CRETE floors are especially resistance to moisture penetration and degradation due to hydrolysis.

THIN-CRETE is available either in pre-colored form or as a tint-able grout mix with a pre-measured colorant pack.

BENEFITS

THIN-CRETE GROUT provides:

- Unique decorative concrete resurfacing system.
- Variety of decorative appearances.
- Interior or exterior applications.
- Easy to use and safe.
- Excellent adhesion to old or new concrete.
- Low water demand.
- Long term durability.

SURFACE PREPARATION

The concrete surface should be free of unbound cementitious by products, loose dirt, oil, grease, or other contamination. Any animal or petroleum contamination should be remove with Increte's GREASE AWAY. Exterior surfaces should be acid etched using a 5 to 1 solution of water to muratic acid.

Interior surfaces should be prepared by mechanical means (shot-blast, sand-blast or by rotary sander). Before installing Thin-Crete all concrete subfloors must be primed with Increte Systems Bond-Crete primer, 1 to 2 coats required depending on substrate profile. (2 coats recommended)

APPLICATION PROCESS

In a clean bucket or paddle mixer (mortar mixer). Add one 50 lb. container of THIN-CRETE GROUT (and THIN-CRETE COLOR PACK ,if applicable) to 4 quarts of cool water while mixing. Once all powder is incorporated, mix for a minimum two –three minutes. Scrape sides and bottom of mixing vessel to be certain all powder is completely wet out. Up to an additional pint of water may be added. Be sure to use the same amount of water for each mix.

RECOMMENDED THICKNESS & COVERAGE

For maximum economy, set gauge rake at 1/8-inch thickness. A single bag of THIN-CRETE should cover approximately 50 ft² @ 1/8-inch, 25 ft² @1/4-inch, or 15 ft² @3/8-inch THIN-CRETE is easily toweled and may be brought to a feather-edge.

Applications over 1/2-inch or use of THIN-CRETE as a concrete patching and repair material may not be economical. However, when used with extender aggregates, THIN-CRETE may be used as an excellent patch/repair compound. After placement the THIN-CRETE surface must reach a plastic state before it is ready for stamping (actual time will vary depending on atmospheric conditions). When ready to stamp apply release agent and perform stamping process per installation instructions. Use THIN-CRETE ANTIQUING COLORANT to add a secondary color effect. For maximum durability and wear resistance, apply one of Increte's

VOC compliant clear sealers. The resulting surface will be a unique **decorative surface.**

COLORS

THIN-CRETE COLORANT COLOR PACKS are available in the 30 standard Increte colors. Pre-colored THIN-CRETE GROUT is available by special order. Custom colors matching for either system is also available. Minimum order quantities may apply.

SAFETY PRECAUTIONS

CAUTION – Do not take internally. If swallowed contact a physician immediately. **KEEP AWAY FROM CHILDREN.**

AVAILABILITY

Available through distributors or contact manufacturer.

IMPORTANT NOTICE

THESE PRODUCTS ARE SOLD SUBJECT ONLY TO THE EXPRESSED WARRANTIES CONTAINED HEREIN. ADDITIONAL WARRANTIES, EXPRESSED OR IMPLIED, AND ANY WARRANTY OF MERCHANTABILITY IS HEREBY EXCLUDED. BUYER AGREES THAT SELLER ASSUMES NO LIABILITY FOR CONSEQUENTIAL DAMAGES OF ANY KIND WHICH RESULT FROM THE USE OR MISUSE OF THE MERCHANDISE SOLD HEREUNDER. IN THE EVENT THAT THE BUYER PROVES THAT ANY GOODS RECEIVED DO NOT CONFORM TO THE SPECIFICATIONS AGREED TO BETWEEN THE PARTIES OR IF THE BUYER PROVES THAT SUCH GOODS WERE DEFECTIVELY MANUFACTURED. THE BUYER'S REMEDIES SHALL BE LIMITED TO EITHER THE RETURN OF THE GOODS AND REPAYMENT OF THE PURCHASE PRICE OR REPLACEMENT OF THE NON-CONFORMING GOODS AT THE OPTION OF THE SELLER. SUCH REMEDY BEING EXCLUSIVE OF ALL OTHERS AND THE SOLE REMEDY AVAILABLE TO THE BUYER, HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES.

WARRANTY

All recommendations, statements and technical data contained herein based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expresses or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his use of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person having any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations or statements other than those contained in written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.