



VIBRA-STAIN CONCENTRATE

PRODUCT NAME

VIBRA-STAIN CONCENTRATE

Manufacturer & Distributor of
Industrial Chemicals
1611 Gunn Highway
Odessa, Florida 33556
(813) 886-8811

PRODUCT DESCRIPTION

VIBRA-STAIN CONCENTRATES are manufactured from blends of concentrated metallic dyes. VIBRA-STAIN CONCENTRATE can be diluted with alcohol, or water as application conditions or environmental restrictions dictate. Each 8 oz container of CONCENTRATE is designed for a 1 gallon mix, but may be adjusted as desired.

BENEFITS

- Add VIBRANCE to concrete!
- VIBRA-STAINS are *not* acid based.
- They are odor-free, easy, and safe to use.
- VIBRA-STAINS may be sprayed, brushed, sponged, or rolled on.
- VIBRA-STAINS are easily blended to create your own custom colors.
- CONCENTRATE may be diluted with water, alcohol or acetone
- Non-hazardous, concentrated color reduces freight costs
- Great for polished concrete

MIXING

Add entire contents of container to 1 gallon of desired thinner (acetone, alcohol or water) and stir.

APPLICATION

Coverage – Coverage will vary with surface condition, porosity, application technique, dilution and desired effects. Average coverage at full strength is 250 to 400 square feet per gallon.

Existing Concrete—All curing agents, sealers, coatings, oils, grease, waxes or water repellants must be removed before application. Surface should be tested to verify its ability to accept the stain. If water beads on the surface, further cleaning, acid washing, stripping or sanding is required.

New Concrete—New Concrete must be cured at least 14 days prior to application of VIBRA-STAIN. COLOR-HARDENER may be used to create different effects and brighter colors. No liquid curing agents should be used. Surface may be acid washed to improve penetration and to produce darker, richer colors.

THIN-CRETE/NEW-CRETE—

Overlays must be allowed to dry completely (24 hours minimum) prior to application of VIBRA-STAIN. Surface may be acid washed to improve penetration and to produce darker, richer colors.

Each surface must be dry, dust-free, prepared and tested. Shake or mix prior to use. Apply with sprayer, brush, roller. Allow surface to dry and recoat, if desired, for a deeper, richer color. Once dry, VIBRA-STAINED surfaces must be sealed to bring out the full effect of the stain. Any of INCRETE'S clear sealers may be used on VIBRA-STAIN including solvent or waterbased sealers, epoxies, or urethanes.

MAINTENANCE

Once sealed a VIBRA-STAIN surface is easy to maintain and can be cleaned by sweeping, washing with commercial floor cleaners, then polishing with a clean cloth or mop. A periodic application of Increte Systems High Gloss Wax – floor wax will ease cleaning and add luster. To preserve the variegated appearance and provide long-lasting durability, apply one of Increte System's Clear Sealers. Periodic reapplication of sealer is recommended when surfaces are subject to high pedestrian or vehicular traffic.

LIMITATIONS

VIBRA-STAINS are for interior use only. Do not apply in areas where they will be exposed to direct sunlight. Fading may result due to UV degradation.

VIBRA-STAINS are translucent and will not cover defects or blemishes in concrete.

Variations in concrete will affect how the surface accepts stain. Always perform a test spot prior to application to be sure the desired effect is possible.

WARNING: USE ONLY AS DIRECTED. Once dye is mixed with alcohol, mixture will be highly flammable. Vapors may cause flash fires. Use only with adequate ventilation. Keep away from heat, sparks or open flames.

KEEP OUT OF REACH OF CHILDREN

IN CASE OF EMERGENCY CALL
1-800-424-9300 (CHEMTREC)

IMPORTANT NOTICE

THESE PRODUCTS ARE SOLD SUBJECT ONLY TO THE EXPRESSED WARRANTIES CONTAINED HEREIN. ADDITIONAL WARRANTIES, EXPRESSED OR IMPLIED, AND ANY WARRANTY OF MERCHANTABILITY IS HEREBY EXCLUDED. BUYER AGREES THAT SELLER ASSUMES NO LIABILITY FOR CONSEQUENTIAL DAMAGES OF ANY KIND, WHICH RESULT FROM THE USE OR MISUSE OF THE MERCHANDISE SOLD HEREUNDER. IN THE EVENT THAT THE BUYER PROVES THAT ANY GOODS RECEIVED DO NOT CONFORM TO THE SPECIFICATIONS AGREED TO BETWEEN THE PARTIES OR IF THE BUYER PROVES THAT SUCH GOODS WERE DEFECTIVELY MANUFACTURED. THE BUYER'S REMEDIES SHALL BE LIMITED TO EITHER THE RETURN OF THE GOODS AND REPAYMENT OF THE PURCHASE PRICE OR REPLACEMENT OF THE NON-CONFORMING GOODS AT THE OPTION OF THE SELLER. SUCH REMEDY BEING EXCLUSIVE OF ALL OTHERS AND THE SOLE REMEDY AVAILABLE TO THE BUYER, HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES.

WARRANTY

All recommendations, statements and technical data contained herein based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his use of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person having any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations or statements other than those contained in written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.