

FROST

Fighter

PORTABLE HEATERS



PORTABLE VENTED HEATERS

- CONSTRUCTION
- INDUSTRY
- MINING
- AVIATION
- AGRICULTURE
- MILITARY



FROST

Temporary Heating Equipment Since 1965

Fighters

ICE

INDUSTRIAL
COMMERCIAL
EQUIPMENT
MANUFACTURING LTD.

1500 Notre Dame
Winnipeg, MB R3E 0P9
TOLL FREE: 1 888 792 0374
DIRECT: (204) 775 8252
FAX: (204) 783 6794
WEB: www.frost-fighter.com
CORPORATE: www.ice-ww.com

Clean, Safe, Economical, High Capacity Heating anywhere you want it!

- Clean burning flame retention burner.
- Vented burning for safe use in confined areas.
- Independent fan and combustion air feeds ensure quick winter starts. No heated air led off for combustion or lost up the flue.
- Service is a breeze.
- Fast parts supply.

Unlike a direct-fired heater, the Frost Fighter provides clean air, free from moisture and contaminated fumes.

Quick connect ducts attach to the front cap outlets and enable the user to disburse the heated air over a large area, with an optional remote thermostat control for maintaining desired temperature levels.

The Frost Fighter is portable and simple to operate – all parts have easy access for quick service and routine maintenance.

With over 35 years of proven reliability and rugged durability even in extreme climates, the Frost Fighter continues to be a leader for temporary heating needs.

Meets OSHA Standards

Specifications

| | IDF 350-11 OIL | IDF 500 OIL | IDF 350 LP/NG | IDF 500 LP/NG |
|---|--|--|--|--|
| CODE NUMBER | 47003 | 47004 | 47005 | 47006 |
| CAPACITY | 320,000 BTUs | 500,000 BTUs | 350,000 BTUs | 450,000 BTUs |
| HEATED AIR (W/OUT DUCT) | 2,500 CFM | 3,100 CFM | 2,500 CFM | 3,100 CFM |
| DISCHARGE TEMP. | 200° F with duct creating 0.4" static pressure | 180° F with duct creating 0.5" static pressure | 220° F with duct creating 0.4" static pressure | 220° F with duct creating 0.5" static pressure |
| FUEL | Fuel Oil* | Fuel Oil* | Propane/ Natural Gas | Propane/ Natural Gas |
| TANK CAPACITY | 35 Imperial – 42 U.S. gallons (18 Hours) | 35 Imperial – 42 U.S. Gallons (14 Hours) | - | - |
| NOZZLE SIZE/ PRESSURE | 2.0 U.S. GPH @ 125 psi | 2.5 U.S. GPH @ 145 psi | LP/NG - 2" w.c. | LP/NG - 3.2" w.c. |
| BURNER MOTOR (115V, 60 CYCLE) | 1/3 HP, 3450 RPM | 1/3 HP, 3450 RPM | 1/3 HP, 3450 RPM | 1/3 HP, 3450 RPM |
| NET WEIGHT (APPROX.) | 400 lbs | 400 lbs | 400 lbs | 400 lbs |
| SHIPPING WEIGHT (APPROX.) | 460 lbs | 460 lbs | 460 lbs | 460 lbs |
| FINISH | Powder Coat | Powder Coat | Powder Coat | Powder Coat |
| AIR OUTLETS - OPTIONAL ONE 16" DIAMETER | Standard - Two 12" diameter | Standard - Two 12" diameter | Standard - Two 12" diameter | Standard - Two 12" diameter |
| DIMENSIONS CRATED (LXWXH) | 70" x 35" x 50" | 70" x 35" x 50" | 70" x 36" x 51" | 70" x 36" x 51" |
| APPROVAL | CSA | CSA | ETL | ETL |

* No. 1 fuel oil or kerosene is recommended when the ambient temperature is less than 8°F (-10°C) Discharge temperature (@50°F ambient). Specifications are subject to change without prior notice.

LP/NG Features: • Quick ball change valve change over from propane to natural gas
• 3 trials for ignition

OIL Features: • Polytank with gauge & environmental spill containment

Your dealer/distributor is: