

# GP 6600A Premium Portable Generator

Item Number: 0620385

# GP 6600A

## Rugged and powerful generators for the most demanding jobsites

>> Designed for construction rental and other demanding applications, these high performance, portable generators deliver unmatched tool starting and voltage regulation in a rugged, compact package. Built the Wacker Neuson way, with heavy-duty frames and premium components to provide long, trouble-free operation even in abusive environments. Ideal for powering high starting amperage tools such as compressors, grinders, fusion welders, saws, pressure washers as well as all of your Wacker Neuson electric- powered pumps, breakers, drills, concrete vibrators, etc. <<



## Additional Advantages

- Best in class tool starting and voltage regulation due to unique step-start generator technology with AVR (automatic voltage regulation) and separate excitation winding.
- Unique GFCI (neutral bonded to ground) sensor system eliminates common GFI outlet failures while offering personal protection on all receptacles including 240 Volt. Meets the latest NEC and OSHA jobsite standards.
- Full wrap-around frame with dual cross-member support, high impact polyethylene fuel tank and heavy duty shock-mounting combine to provide outstanding impact protection.
- A super quiet muffler allows for versatile operation.
- Unique auto-idle control with time delay system automatically reduces the engine to a low speed reducing fuel consumption, noise and wear.
- The folding central lifting eye and integrated wheel kit make these compact generators easy to transport and store.
- Full power switch for maximum 120V power output or 120V/240V power.
- Features reliable Honda OHV engine with low oil shutdown.



Description	Metric	Imperial
Length x width x height	685 x 530 x 530 mm	27 x 21 x 21 in
Dry Weight	87 kg	192 lb
Shipping weight (including packaging)	89 kg	197 lb
Shipping size	711 x 546 x 589 mm	28 x 21.5 x 23 in
Maximum output	6600 W	6600 W
Continuous Output	6000 W	6000 W
Continuous AC amps	50 / 25 A	50 / 25 A
Voltage A.C.	120 / 240 V	120 / 240 V
AC circuit breaker amps		27
Frequency	60 Hz	60 Hz
Phase	1 ~	1 ~
Power factor (1 phs / 3 phs)	1	1
Engine Type	Honda GX390K1	
Starting system	Recoil	Recoil
Displacement	389 cm <sup>3</sup>	24 in <sup>3</sup>
Max. Rated Power at Rated Speed*	8.2 kW at 3600 rpm	11 hp at 3600 rpm
Operating speed	3600 1/min	3600 rpm
Power Rating Specification	SAE J1349	SAE J1349
Fuel tank capacity	19 l	5 US gal
Running time/full load	5 h	5 h
AC outlet receptacles	(2) -125V, 20 A Duplex, (1)- 125V, 30 A Twist Lock; (1) - 125/250V, 20 A Twist Lock	(2) -125V, 20 A Duplex, (1)- 125V, 30 A Twist Lock; (1) - 125/250V, 20 A Twist Lock

### Standard Package - GP 6600A

Include operator's manual and parts book. Some standard packages include wheel kit. Battery sold separately.

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Friday, July 2, 2010

