



# 1330SE

## Micro Scissor Lift

- 13 ft. (4 m) platform height and 19 ft. (6 m) working height
- Fits on most elevators with shortest overall length and low GVW
- 24 in. (60 cm) roll-out deck extension with incremental lock positions
- Direct electric drive for exceptional duty cycle
- 2 person platform with 530 lbs (240 kg) capacity
- Drivable at full height
- Fully proportional lift and drive controls
- Ultra compact design fits into small and tight work areas
- Compact size without compromising generous work area



**Lightweight, Micro Slim Scissor with True Slide-Out Deck**

## Features

### Work Area

Roll-out deck extension with incremental locking positions  
 Standard full height swing gate  
 Lanyard attachments (2)

### Performance

Direct electric drive  
 Fully proportional drive and lift controls

### Power

24v 85Ah DC electric power  
 Battery charge indicator

### Serviceability

Lubrication-free scissor bearings  
 Easy maintenance access to mechanical and electrical components in a slide-out tray  
 Logically grouped components and numbered wiring for easy reference

### Safety

Dedicated compartment protects electrical and hydraulic components  
 Emergency shut-off at platform and lower controls  
 Non-skid metal deck construction  
 Descent alarm  
 Drive speed interlock  
 Multi-axis tilt sensor  
 Scissor maintenance lock  
 Multiple disc brakes

### Other Features

Removable upper controls  
 Voltage-compensating fully automatic battery charger  
 Hour meter  
 Machine tie downs  
 Non-marking tires  
 All motion alarm  
 Fork lift pockets

## Optional Features

Flashing beacon (continuous)  
 2-Year extended warranty



### MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA  
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520  
 Email: info@MECawp.com | www.MECawp.com

97010 DTD 1016

1330SE	U.S.	Metric
<b>Heights</b>		
Working Height*	19 ft.	6 m
Platform Height	13 ft.	4 m
Stowed Height (Top Guardrail)	74 in.	1.9 m
Stowed Height (Rails Folded)	N/A	N/A
Stowed Height (Platform Floor)	35 in.	.9 m
Guardrail Height	39 in.	1 m
Toeboard Height	6 in.	15 cm
Ground Clearance (Stowed)	2.5 in.	6 cm
Ground Clearance (Elevated)	0.6 in.	1.5 cm
<b>Dimensions</b>		
Length-Stowed (Overall)	58 in.	1.5 m
Length-Stowed (Ladder Removed)	51 in.	1.3 m
Chassis Width	30 in.	76 cm
Platform Length (Extended)	75 in.	1.9 m
Platform Length (Retracted)	51 in.	1.3 m
Roll-Out Deck Length	24 in.	60 cm
Platform Width	27.5 in.	70 cm
Wheelbase	41 in.	1.0 m
Total Lift Capacity	530 lb	240 kg
Personnel Capacity	2	
Roll-Out Deck Capacity	250 lbs	113 kg
<b>Speed</b>		
Raise/Lower Speed	20 s / 20 s	
Drive Speed (Stowed)	2.5 mph	4.0 km/h
Drive Speed (Elevated)	0.5 mph	0.8 km/h
<b>Performance</b>		
Gradeability	25%	
Turning Radius (Inside)	18 in.	.45 m
Weight**	1,900 lbs.	860 kg
Power Source	24 v DC, 85Ah Battery pack	
Controls	Proportional drive & lift controls	
Tires	9 in.	23 cm

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.  
 \*\*Weight may vary with certain options or configurations.

**Important** - MEC scissor lifts must be on a hard level surface while elevated.

**Warranty** - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

**Meets or exceeds** the requirements of ANSI A92.6-2006 and CSA B354.4-02.

**Specifications** subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by:

